

# J&S Technical Information

## Oil Pressure Tester - G6710E



### Instructions

With engine switched off remove the oil pressure sender unit / switch.

Choose the correct adaptor and fasten it into the sender port. Screw the test gauge pipe into the adaptor until firmly seated. This is a tapered thread and will seal itself.

Start the engine and having made sure there are no leaks at the system joints, read the oil pressure from the gauge.

Switch off engine and allow the oil pressure to drop to zero before removing the gauge from adaptor and then remove the adaptor from the test port. Take care when removing the gauge and adaptors as they may have become hot during the test.

Replace switch / sender unit before starting the engine again.

# OIL PRESSURE TESTER - APPLICATIONS

ALFA ROMEO	All models	8
AUDI	All models	6
AUSTIN ROVER	All models	2
BEDFORD	Viva HA van	3
	Astra van	8
	Chevanne	3
	CA & CF vans	3
	1600 pickup	1
	Midi 2200	1
BMW	All models	7
CITROEN	CX all models	8
	Visa 1600 , BX all	9
	Visa652 GS Ami	7
DAIHATSU	Charade turbo	1
FIAT	500 600	7
	850	7
	124	7
	125	8
	126	8
	127	7
	128 130 131 132	7
	Panda	8
	Uno Strada Argenta	8
	Regata	8
	X1/9	8
FORD	Granada 2500 3000	2
	Transit V4	2
	Transit ohc ohv	3
	All other models	3
FREIGHT-ROVER	Sherpa	2
	285 , 310 , 350	2
HONDA	All models	1
HYUNDAI	All models	1
ISUZU	All models	1
JAGUAR	All models	2
LADA	All models	8
LANCIA	All models	8
LAND ROVER	All excluding V8	4
	V8	5
MAN TRUCKS	All models	10
MAZDA	All rwd	1
MERCEDES BENZ	220 230 250 280	6
	200	8

MERCEDES TRUCKS	All models	10
MG	Maestro 1600	1
	MGBGT V8	5
	All others	2
MINI	All models	1
NISSAN	Cherry 1200 1350	8
	All others	1
OPEL	All models	8
PEUGEOT	205 205D	9
	305GL 1290	9
	305GL GLR 1290	8
	305 GLS SR SRR diesel	9
	505i	7
RELIANT	Kitten Robin Rebel	2
	Regal Rialto	2
	Schimitar 76-	3
RENAULT	R9TD R9TDE diesel	10
	R11GTD	10
	R11TDE diesel	10
	All others	8
ROVER	2000 , 2200	4
	2300 , 2600	4
	2000 , 2300 ,2600sdi	3
	2400 diesel	6
	3.5 V8	5
	213 , 820i	2
	216 , 825i , Sterling	1
SAAB	900	3
	All others	2
SKODA	All models	6
SUBARU	All models	1
SUZUKI	All models	1
TOYOTA	All models	1
TRIUMPH	Acclaim 81-84	1
	All others	2
VAUXHALL	All models 80-	8
VOLKSWAGON	L28-35 diesel van	2
	All others	6
VOLVO	4 cyl models	2
	Trucks	10
	Volvo Daf all models	8



## ADAPTORS

NUMBER	THREAD	NUMBER	THREAD
1	1/8 DIN	6	M10 X 1.0
2	1/8 X 27 NPT	7	M12 X 1.5
3	1/4 X 18 NPT	8	M14 X 1.5
4	3/8 X 20 UN	9	M16 X 1.5
5	1/2 X 20 UNF	10	M18 X 1.5

Adaptor No.2 is permanently fitted to the hose end, and fits into all the other adaptors.